



Granular (Pallets) Weighing / Filling Machine



Applications	<ul style="list-style-type: none">• Filling of Granules and Dry and Free-Flowing Powder
Features	<ul style="list-style-type: none">• Simple Operation and Easy Handling• Microprocessor Weighing System• Encased Construction with Aspiration Sprout• Screw Feeder allows High Rate Product Conveyance into the bag



Technical Specifications	
Model	VC 505- NWF- VB
Display Graduation	1 Part of 3000 Full Scale
Accuracy	<± 0.5% of Full Scale
Material of Construction	Mild Steel with Epoxy Paint Powder Coated Finishing
Weighing Controller	VC 505 Indicator, Virtual Measurements & Control Inc, USA High Resolution 64 x 240 mm LCD, 1.25 x 5 inch Graphic Display with 0.8 inch digital and 60 character text. 17 Buttons Membrane Keypad with Tactile Keys RF/ EMF Protection Selectable Low Pass Filter and Adjustable Averaging Back-up memory (in case of power failure) 10 Product Memory
Control Features	2- Stage Control Valve for Fast Filling and Slow Filling Free-fall/ Auto Free Fall Compensation Selection Automatic Tare Function Restart/ Resume Mode Auto/ Manual Mode Automatic Zero Tracking Safety Interlock (in case of power failure)
Load Cell	VLC-132 series, Virtual Measurements & Control Inc, USA Single-point, Analog Load Cell IP 65 Protection against Moisture Ingression Aluminum construction
Options	Inlet Product Rotary Fluidizing Unit Feed Unit: Rotary, Gravity or Vibratory System Print Output c/w Panel Mounted 50mm Dot Matrix Printer Stainless Steel Construction
Container Weight (kg)	Fill Rate (Bag/ Hr)
5~50	220 – 160